

## FEATURES

- Meets or exceeds requirements of UL Standard 8 and Standard 711
- Meets requirements of NFPA 10, 1998 Edition
- Simple operation and maintenance
- Easy to use extension wand for greater safety
- Rechargeable
- Sold and serviced through an international network of independent distributors in every state and most foreign countries
- ULI rated 2-A:C:K
- ULC rated 1-A:C:K



# HAND PORTABLE EXTINGUISHER DATA SHEET

## APPLICATIONS

The K-Guard™ liquid agent fire extinguisher is specifically designed for use on fires that involve combustible cooking vegetable or animal fats in commercial cooking equipment. Typical appliances include; fryers; griddles, range tops; upright, natural charcoal, or chain-type broilers; electric, lava rock, mesquite or gas-radiant char-broilers and woks.

Newer, more efficient cooking appliances, plus the use of non-saturated cooking oils, require a fire extinguishing agent which will not only smother a fire but provide a cooling effect.

The extinguisher is ideally suitable for use in restaurants, hospitals, nursing homes, hotels, schools, airports, and other similar facilities.

It is normally used as a back up to an automatic fire suppression system.

The energy source to the cooking equipment is to be shutoff in order to attain complete extinguishment and permit the cooking media to cool below its auto-ignition temperature.

## DESCRIPTION

The K-Guard extinguisher is an attractive, easy to use and maintain, stainless steel extinguisher which has a special extension wand and a non-disruptive spray nozzle. This feature allows the user to stand back at a safe distance while applying the agent to a cooking surface.

The PRX fire extinguishing agent used in the extinguisher is a specially-formulated, aqueous solution of inorganic salts. It has been developed to provide rapid flame extinguishment and securement of hot fuels such as cooking shortenings.

## CODES

Meets new Class K (Combustible Cooking Media) fire requirements of NFPA 10.

# K-GUARD™ MODEL LA-0191 EXTINGUISHER

## SPECIFICATIONS

- |   |                          |
|---|--------------------------|
| • Model No.                                   | LA-0191                  |
| • ULI Rating                                  | 2-A:C:K                  |
| • ULC Rating                                  | 1-A:C:K                  |
| • Capacity                                    | 6 liters of PRX Agent    |
| • Extinguisher Height                         | 19 in. (48.3 cm)         |
| • Height With Hose and Wand Installed in Clip | 30 in. (76.2 cm)         |
| • Width With Hose and Wand Installed in Clip  | 14 in. (35.6 cm)         |
| • Depth (Diameter)                            | 7 in. (17.8 cm)          |
| • Range                                       | 10-12 ft. (3.1-3.7 m)    |
| • Discharge Time                              | Approximately 40 seconds |
| • Bracket                                     | Wall Mount               |

## ORDERING INFORMATION

Description	Part No.
K-Guard Model LA-0191 Liquid Agent Fire Extinguisher	426018
5 Gallon Container PRX Liquid Agent (Fills three LA-0191 extinguishers)	423320